

# SKK9500

Flexible window curtain track



## SKK9500 Flexible window curtain track

### Features:

The SKK9500 flexible window curtain track has been developed in response to UK Government requirements and is constructed from a specially formulated plastic which is lightweight and strong, and utilises self-lubricating gliders for ease of use in all hand-drawn curtain applications. Tests have shown that for anti-ligature purposes it is most important that the complete track collapses leaving no point of ligature. Even where a fixed track provides no ligature points, heavy weights can be suspended from the curtains which in turn is a serious potential risk. With the SKK9500 the track and curtain together will part from the SK brackets under abnormal load and can then be simply and quickly reinstated. Only for use with lightweight curtains and where the risk of violence precludes the use of the standard SKK6200 aluminium track.

### Benefits:

Developed from a specially formulated plastic construction the SKK9500 is specially designed to be flexible enough to prevent its use as a weapon by prisoners or violent psychiatric patients, and shatter resistant to reduce the risk of sharp edges. Suitable for lightweight curtain usage, and an excellent alternative to aluminium tracks when the threat of violence restricts usage of metal products. Offering both wall-fix and top-fix options to blend in well with any environment whilst remaining pleasing to the eye, this white flexible plastic window curtain track with special low friction gliders satisfies the most demanding of environments, whether it be residential or commercial. Secured by magnetic brackets for 100% fail-safe\* anti-ligature functionality and in use in many mental health environments worldwide.

### Specification:

The magnetic anti-ligature SKK9500 flexible hand drawn window curtain track. White plastic track of special flexible plastic formulation complete with gliders at 16 per metre and magnetic wall-fix or top-fix brackets as necessary, spaced in accordance with manufacturer's recommendations. Fitting to be carried out by trained and accredited personnel.

### O+M Guidance

It is an NHS requirement that items suspended on load-release support systems should be maintained and load-tested in accordance with the manufacturer's instructions on an annual basis. The SK system is maintenance-free and its performance remains constant even after repeated use. It is a requirement, however, to carry out a physical inspection and testing of YewdaleKestrel® fittings to identify any possible damage or evidence of tampering and undertake an annual load test. Annual testing should only be carried out by Protects Plus 0345 646 0955.

Width Inches	Width mm	No. of Brackets
19 <sup>3/4</sup>	500	2
35 <sup>1/2</sup>	900	3
51	1300	4
67	1700	5
82 <sup>3/4</sup>	2100	6
98 <sup>1/2</sup>	2500	7
114	2900	8
130	3300	9
145 <sup>1/2</sup>	3700	10



Find this product on NBS Source



This product range comes with a full Lifetime Warranty as standard.