

# KVL3 1

4PM, PNGPSU\*<sup>®</sup> <sup>®</sup> Premium wand



## 4, KVL31 Premium wand

### Features:

The 4, 4MUFNT<sup>®</sup> 4, KVL31 premium vertical blind, with added wand control, provides a safe solution for a host of anti-ligature shading requirements. Incorporating 40 x 25mm premium profiled white aluminium head-rail and wheeled replaceable plastic carrier trucks, and magnetic wall-fix/top-fix brackets. This ensures that, under excess load, the head-rail separates from the brackets leaving no remaining points of ligature - a highly essential safety feature. The constant transport of the louvres is guaranteed by the precision made aluminium spindle shaft. Wand control operation with built-in slip clutch for louvre tilt. 127mm or 89mm louvres available - all with enclosed louvre weights.

### Benefits:

Robust with high quality performance, whilst remaining pleasing to the eye, the 4, KVL31 makes an excellent choice for many sectors. The comprehensive truck options satisfy the most demanding of environments whether it be residential or commercial. The utilisation of the wand control provides the ultimate cord/chain-free solution and offers exceptional ease of use. The control mechanism is enclosed within the head-rail and supported on a sturdy, aluminium back bar, secured by magnetic brackets for 100% fail-safe\* anti-ligature functionality. With enclosed louvre weights as standard throughout to remove any individual loose part issues.

### Options:

Spring metal trucks; ball and chain control (4, KVL30).

### Specification:

The magnetic anti-ligature 4, 4MUFNT<sup>®</sup> 4, KVL31 vertical blind with added wand control. 127mm or 89mm louvres in flame retardant fabric from the YewdaleDefiant<sup>®</sup> range, fixed to replaceable wheeled truck hooks and accommodating enclosed louvre weights throughout. Premium 40 x 25mm white powder-coated head-rail with wand control operation and built-in slip clutch. Secured by magnetic wall-fix/top-fix brackets spaced in accordance with manufacturer's recommendations. Fitting to be carried out by trained and accredited personnel.

4M, PNGPSU\*<sup>®</sup> 4, KVL31 is the only approved premium wand control vertical blind system to be used with YewdaleKestrel<sup>®</sup>

## Vertical Blinds Specification Guide

Vertical blinds	Min Width*	Max Width	Max Drop	Max M <sup>2</sup>
4, KVL31	300	2800	3200	8.0

Sizes shown in millimetres. Based on fabric weight of 220g/m<sup>2</sup>, e.g. Thames. Use of heavier fabrics may require appropriate reductions. \*Where adjacent blinds are fitted with YewdaleKestrel<sup>®</sup>, there should be no more than 2 brackets within a total distance of 700mm.



Find this product on NBS Source



This product range comes with a full Lifetime Warranty as standard.