SK K4840

SK SafeDoor







romfor

teriors

SK SafeDoor

Features:

The SK SafeDoor is constructed from a lightweight 4kg soft foam then coated with a resilient antimicrobial, stain resistant faux leather material and easy clean PVC coated webbing, designed to withstand daily patient and client use in hospital and mental health environments. By harnessing the natural forces of short range magnetism for its fixing Points, it eliminates all anchor points usually associated with doors and hardware. This ensures that, under excess load (9kg), the door separates from the door frame to which it's mounted leaving no remaining points of ligature - a highly essential safety feature. For those requiring an ensuite door that self closes, there is the added option of a new patented selfclosing hinge so the door always returns to a closed position.

Benefits:

An en-suite door with zero ligature risk makes the SK SafeDoor the only choice in providing acceptable levels of privacy and dignity yet still ensuring no risk. Designed with a strong focus on being lightweight for both service user and staff protection, this durable tear and stainresistant solution is both waterproof and flame retardant as standard. Easy to clean and PVC webbing material to prevent infection. Its external surface can be printed on to suit the décor of the environment. Incorporating the proven qualities of SK magnetic fixing properties means that this also has 100% fail-safe* anti-ligature functionality. Simple to install.

Options:

Left hand or right hand hinge mounted; Selfclosing hinge; PVC coated side webbing and door latch, 1000mm width plus other sizes to order; colour/image of your choice.

Specification:

The magnetic anti-ligature SK SafeDoor for en-suites with vandal resistant, soft foam core. Manufactured from flame retardant fabric, constructed using anti-pick, tamper resistant materials, and incorporating Biosafe antibacterial formula to withstand vigorous daily use in hospital and mental health environments. The 4kg tear/ stain resistant door is anti-static and will fall away from its magnetic fixing plates when subjected to a load greater than 9kgs.

0+M Guidance

It is an NHS requirement that items suspended on load-release support systems should be maintained and load-tested in accordance with the manufacturer's instructions on an annual basis. The SK system is maintenance-free and its performance remains constant even after repeated use. It is a requirement, however, to carry out a physical inspection and testing of YewdaleKestrel® fittings to identify any possible damage or evidence of tampering and undertake an annual load test. Annual testing should only be carried out by Protects Plus 0345 646 0955.

Three year warranty as standard. SafeDoor is excluded from the lifetime warranty.



Find this product on NBS Source