

# PUMA

- Robust blackout fabric with reliable hanging characteristics
- Oeko-Tex® Standard 100 certified, free from harmful substances
- Greenguard® certification for low-emission products

## APPLICATIONS



Not suitable: SG 4905,  
SG 4900, SG 4907



## FABRIC PROPERTIES

● Blackout

⌘ 25% glass fibre, 75% PVC coated

Ⓢ 407 / 530 g/m<sup>2</sup>

⊥ 0.30 / 0.38 mm

← max. → 239 / 295 cm

📏 244 cm, 300 cm

## FEATURES / TECHNICAL PROPERTIES

☀ 6

🔥 Flame retardant

💧 Applicable in humid areas

🖨 Digital printing

🌿 Oeko-Tex, Greenguard

🎨 Special colours from 1'500 m

📌 Weldable

## WASHING INSTRUCTIONS



## FLAME RETARDANT

Class 1 (CSE RF)  
M1 (NF P 92-503/5/7)  
Type B (BS 5867-2)



**Puma**
**OPTICAL AND SOLAR COEFFICIENTS ( $\pm 5\%$ , DIN EN 410)**

Colour	$R_s$	$A_s$	$F_c$	$g_{tot}$
<b>900</b>	56.0	44.0	0.56	0.40
<b>909</b>	22.0	78.0	0.78	0.56
<b>930</b>	5.0	95.0	0.89	0.64
<b>933</b>	45.0	55.0	0.63	0.45
<b>934</b>	60.0	40.0	0.54	0.39

 **$R_s$**  Solar reflectance

 **$A_s$**  Solar absorption

 **$F_c$**  Shading factor

 **$g_{tot}$**  Total g-value

 $F_c + g_{tot}$ : Value calculated with glass:  $0.72 / U_g = 1.6 \text{ W/m}^2 \text{ K}$ , DIN EN 13363-1


Colours shown are not binding