SK SafeDoor 2









YewdaleKestrel® SafeDoor 2







Crib 7 fire rating BS 5852:2006



Single or double sided print



Fabric is reinforced by fibreglass



Seems are welded and sewn for added security

Features:

Although the SK SafeDoor 2 may look different, •Self-closing patent-pending hinge it is backed by the same safety features as our original SK SafeDoor, with a number enhancements. This load release anti- •Colour/image of your choice ligature en-suite door continues to use our trusted load release magnets for guaranteed break away, whilst offering additional benefits including a higher fire rating and added defence against tampering.

Benefits:

For greater security and long-term durability, the SK SafeDoor 2 offers the added protection of welded and sewn pockets which keep the magnets secure and prevent tampering.

Improved fire retardant properties adhere to strict fire p revention g uidelines (Crib 7 fi re rating - BS 5852: 2006)

The SK SafeDoor 2 has an attractive curved profile that is just 9mm thick, making it lighter than our first SK SafeDoor. The soft foam door poses minimal risk of injury and greatly reduces the risk of the door being damaged.

The fibreglass material ensures the image is free and dignity whilst allowing observational physical checks.

images on a durable, wipe-clean surface. Plus 0345 646 0955. Water-resistant materials that are ideal for en-suites. We offer a fast turnaround time of 5 to 7 business days.

- •Left hand or right-hand hinge mounted
- Single or double-sided print

Specification:

en-suites with vandal resistant, soft foam core. products only. Care should be taken Manufactured from flame retardant fabric, when assessing or arranging a room to constructed using anti-pick, tamper resistant ensure that SK products cannot be materials, welded and sewn pockets, and misused in conjunction with any other incorporating Biosafe antibacterial formula to item, furniture or fixings in the room. It is the withstand vigorous daily use in hospital responsibility of the end user or client to and mental health environments. The 4kg ensure the product is suitable for the tear/stain resistant door is anti-static and will environment it is being installed fall away from its magnetic fixing plates when in. SK products must be fitted by a qualified subjected to a load greater than 9kgs.

0+M Guidance

It is an NHS requirement that items suspended on effectiveness as an anti-ligature system. load-release support systems should be Three year warranty as standard. maintained and load-tested in accordance SafeDoor 2 is excluded from the lifetime with the manufacturer's instructions on an warranty. annual basis. The SK system is maintenanceand its performance vastly improved, long-lasting and a lot harder constant even after repeated use. It is a to puncture. Maintains service user privacy requirement, however, to carry out a inspection and testing YewdaleKestrel® fittings to identify any possible damage or evidence of tampering Single or double-sided print available, and undertake an annual load test. Annual facilitating the introduction of calming testing should only be carried out by Protects

Safety Note

Sensitive electronic equipment may be damaged by proximity to a magnetic field and should not come within 150mm of the underside of the brackets. Any load-release device, by its nature, may cause damage when operated. Articles suspended magnetic the SK anti-ligature system will come down when pulled.

The magnetic anti-ligature SK SafeDoor 2 for $_{
m SK}$ products are designed as standalone Professional following the manufacturer's instructions. Failure to do so could jeopardise the product's



Find this product on NBS Source