

SKKR20S

Slow-rise spring



SKKR20S Slow-rise spring

Features:

The SKKR20S spring roller blind with a brake to ensure a slow, smooth and quiet operation. White metal universal brackets fitted to white aluminium back bar for face, top or side fixing with 32mm grooved aluminium barrel. Fabric is locked into a groove in the barrel, and features a white tear drop aluminium bottom bar with cord pull as standard. This system uses magnetic wall-fix/top-fix brackets. This ensures that, under excess load, the back bar separates from the bracket leaving no remaining points of ligature.

Benefits:

Smooth and quiet operation makes the SKKR20S an excellent choice for a vast range of applications. The SKKR20S braked spring blind provides the ultimate cord/chain-free solution and offers exceptional ease of use. The slow-rise spring is enclosed within the barrel and supported by sturdy, attractive metal brackets. Fitted to white aluminium back bar and secured by magnetic brackets for 100% fail-safe* anti-ligature functionality. Fabric is locked into the barrel and bottom bar maintaining exceptional edge to edge coverage for even better shading properties.

Options:

Spring limit stop; Alternative bottom bars, including fully fabric covered, in aluminium or plastic, and aluminium Tear Drop in black or silver.

Specification:

The magnetic anti-ligature SKKR20S braked spring control roller blind with vandal resistant, cord/chain-free braked spring. Flame retardant fabric from the YewdaleDefiant® range, locked into grooved 32mm aluminium barrel along with white Tear Drop aluminium bottom bar. Slow-rise spring and braked spring end housed within aluminium barrel supported by white metal brackets, and fitted to white aluminium back bar, secured by magnetic wall-fix/top-fix brackets spaced in accordance with

manufacturer's recommendations. Fitting to be carried out by trained and accredited personnel.

O+M Guidance

It is an NHS requirement that items suspended on load-release support systems should be maintained and load-tested in accordance with the manufacturer's instructions on an annual basis. The YewdaleKestrel® system is maintenance-free and its performance remains constant even after repeated use. It is a requirement, however, to carry out a physical inspection and testing of YewdaleKestrel® fittings to identify any possible damage or evidence of tampering and undertake an annual load test. Annual testing should only be carried out by Protects Plus 0345 646 0955.

Roller Blinds Specification Guide

Roller blinds	Min Width*	Max Width	Max Drop	Max M ²
SKKR20S**	450	1850	2450	4.3

Sizes shown in millimetres. Based on fabric weight of 220g/m², e.g. Thames. Use of heavier fabrics may require appropriate reductions. *Where adjacent blinds are fitted with YewdaleKestrel®, there should be no more than 2 brackets within a total distance of 700mm. **Use of limit stop may require appropriate reductions.



Find this product on NBS Source



This product range comes with a full Lifetime Warranty as standard.