

# SK R56 Overhead Crank

Roller Blinds



sol  
komfort  
interiors



## R56 Overhead Crank

### Features:

The SKR56 overhead roller blind system with crank operation. White aluminium brackets for top or face fixing with 50 and 57mm grooved aluminium barrels. Fabric is mounted onto a sprung 57mm aluminium barrel whilst at the other end it is fitted to a white Tear Drop aluminium bottom bar, attached to two draw tapes. These tapes are attached, between flanged guides, to the 50mm drive barrel, operated by 1:4 gear control mechanism and crank handle.

### Benefits:

The SKR56 roller blinds are the ultimate in choice for the shading requirements for sloping or horizontal roof windows. With heavy duty componentry and a powerful spring action to the fabric roller, these blinds may be confidently specified for awkward or inaccessible locations. The magnetic detachable crank handle provided with the R56 removes the common issues associated with locating the drive at height and solves the problem of unauthorised use.

### Options:


Tear Drop aluminium bottom bar in black or silver; Channel side-guiding system; Fixed crank handle.

### Specification:

SKR56 crank operation overhead roller blind with 1:4 geared crank mechanism. Flame retardant fabric from the SK range, on 57mm aluminium barrel with enclosed spring attached to white Tear Drop aluminium bottom bar as standard. 50mm drive barrel connected to gear control crank mechanism operates blind by means of draw-tapes to the bottom bar. Supported by sturdy, attractive brackets and incorporating magnetic detachable crank handle.

## Roller Blind Specification Guide

Model	Min Width	Max Width	Max Drop	Max M <sup>2</sup>
R56 Overhead Crank	720	2500	2000	4.0



This product range comes with a full Lifetime Warranty as standard.